

LOVE what you PRESS!

DecoFILM®



★Brilliants will not stretch or layer







Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Specialty Materials
THE BEST GARMENT DECORATION PRODUCTS

LOVE what you PRESS!

DecoFILM®

- The "Brilliant" styles offer a smoother, chrome-like surface
- The "Super" styles offer a slightly softer hand and stretchability
- Add value to your fashion designs with the brilliant accent of reflective metals
- Super Silver, Super Gold, and Super Copper are Oeko-Tex Class II Certified

Application Instructions

Adheres to cotton, uncoated polyester, fabric blends, wool



45° Blade for Supers

60° Blade for Brilliants with high pressure



Cut this material in mirror image



310°F - 330°F



Firm, even pressure, cover and reheat if necessary



10 - 15 seconds



Peel cold



Super Silver, Gold, and Copper - Wash inside out, gentle cycle, cold water, tumble dry low. Suitable for dry-cleaning.

All others - Hand wash only.

No nylon.

Warning: Super Silver and Super Gold:

In order to avoid any color fading after washing, you must press the material with silicone paper for an additional 3 seconds, if not, the washing resistance is considerably reduced, therefore any claims regarding color fading **WILL NOT** be acknowledged in the future.

Instructions for application to moisture-wicking materials:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then gently apply it to the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

Instructions for application to dazzle cloth & shiny polyester materials:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2015, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107