

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS




LOVE what you PRESS!



FROSTY CLEAR

- Thin and transparent UV-resistant polyurethane film with a semi-matte finish
- Durable, weeds easily, and has a soft hand and strong grip
- Manufactured without the pressure-sensitive carrier for easy stacking
- Use with decorative lines to add value and pop to your designs



Frosty Clear PLS-9000



[See reverse for application instructions](#)

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2013, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS



LOVE what you PRESS!



Applications

Cotton, Uncoated Polyester, Cotton/Polyester, Polyester/Acrylic



45° Blade



Cut this material in mirror image



330°F - 335°F



Medium to firm, even pressure



17 - 20 seconds



Peel cold then cover with Teflon sheet and repress for 5 seconds



Wash warm, tumble dry normal. Suitable for dry-cleaning.

No nylon. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.

* Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester routinely causes adhesion issues.

* Instructions for application to moisture-wicking fabrics:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then rub it into the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.



Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2013, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107