

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS



LOVE what you PRESS!



ThermoFlex®SPORT

					
White SP-4100	Storm Grey SP-4150	Black SP-4236	Red SP-4301	Orange SP-4333	Maroon SP-4350
					
Athletic Yellow SP-4426	Navy Blue SP-4513	Royal Blue SP-4522	Columbia Blue SP-4576	Purple SP-4584	Kelly Green SP-4633
					
Dark Green SP-4676	Old Gold SP-4843	Neon Pink SP-4910			



Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2013, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107

SPORT

ThermoFlex[®]SPORT

- Bridges the gaps in open-mesh athletic jerseys
- Durable, thick, and weeds easily
- Pressure-sensitive carrier enables repositioning
- Presses at low temperature for shorter time

Application Instructions

Adheres to Cotton, Uncoated Polyester, Mesh, and Poly-blend fabrics



45° Blade



Cut this material in mirror image



300°F - 320°F



Medium even pressure



8 - 10 seconds



Peel warm or cold



Wash cold with normal settings. Air fluff or line dry.

No nylon. These materials cannot be layered. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. This is a PVC product, which emits hazardous fumes when cut with a laser machine!

*Instructions for application to moisture-wicking materials:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then rub it into the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

*Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.

*** These materials cannot be layered**

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2013, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107