Specialty Materials THE BEST GARMENT DECORATION PRODUCTS

LOVE what you PRESS!





- Same qualities as Plus but without the pressure-sensitive carrier
- Allows for easy stacking of weeded designs
- Great for doing pre-cut team lettering and numbers
- Durable and weeds large designs easily



Application Instructions

Cotton, Uncoated Polyester, Fabric blends, Spandex, Lycra, Wool, Linen



45° Blade



Cut this material in mirror image



315°F - 320°F



Medium to firm, even pressure



15 seconds



Let cool for 7 seconds then peel



Wash warm, tumble dry normal.

No nylon. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.

* Instructions for application to moisture-wicking materials:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then rub it into the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

* Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2015, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107