

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS



LOVE what you PRESS!



ColorJET III™ Dark

Digital Media for Textile Transfers

Designed for water-based/pigmented desktop inkjet printers



Heat Transfer Sheets CJ3-2175

One step printing for dark fabrics using your desktop inkjet printer.

Use inkjet “print and cut” system or cut by hand.

Can be applied with a hand iron.

Available in two sizes: 8.5” x 11” or 11” x 17”

Application Instructions

Adheres to Cotton, Uncoated Polyester, Fabric Blends, Satin



Print and cut this material “right-reading.” Remove image from release liner and place printed side up.



No transfer mask necessary. Use **silconed** sheet.



375°F



Medium to Firm, even pressure



25 seconds



Peel silicone sheet when cool



Wait 24 hours before washing. Wash inside out, gentle cycle, warm or cold water, tumble dry. Not suitable for drycleaning. No bleach or aggressive cleaning agents.

No nylon, dazzle cloth, shiny polyester, or moisture-wicking materials. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. Make sure that the print is thoroughly dry before pressing!

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2015, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107

ColorJET III™ Dark

IMPROVED FOR DESKTOP PRINTING FOR DECORATING DARK TEXTILES

**Available in 8.5" x 11" and 11" x 17" sheets for desktop use.
Prints on most ink jet printers with no special inks required!
Use ink jet "print and cut system" or cut by hand.**

APPLICATION INSTRUCTIONS

PRINTING - The print side is the blank side of the sheet. Follow your printer instructions for loading the sheet and feed one sheet at a time. Print in "right-reading." Remove the image from the release liner and place printed side up. Make sure the print is thoroughly dry before pressing. Use a silicone sheet to transfer the image to the garment.

Suggested Printer Settings:

HP - Iron on transfer at normal or best quality
Epson - 300 dpi ink jet paper or plain paper at 300 or 720 dpi
Epson Stylus Photo - Quality: Best Photo, Paper Type: Presentation Paper Matte
Canon - T-Shirt transfer at default settings
Lexmark - Iron on transfer at best quality either 600 or 1200 dpi

NOT RECOMMENDED for use on HP1200C pr 1600 C

Do not leave a margin around the edge of the image. Any white material that is left will be transferred to the garment. Round the edges, when possible, to improve adhesion. Carefully remove the paper backing by tearing a corner and peeling away the excess white material.

HAND IRONING - Preheat iron to highest setting, empty water, and set to the dry setting. Iron the shirt to remove all wrinkles. Iron on a safe, flat surface, such as a counter top. DO NOT iron onto wood, glass, or metal surfaces. Place the transfer face up on the garment with the siliconized sheet on top. Iron using light pressure, in straight vertical & horizontal lines, over the entire image. A full 8.5" x 11" sheet requires 1.5 minutes of ironing, while a half sheet requires 1 minute.

IRON A SECOND TIME using **FIRM PRESSURE** and the same technique as before. Let fabric cool completely and then slowly peel the ironed sheet in an even motion.

HEAT PRESS - Set the heat press to 375°F. Press fabric to remove wrinkles. Allow the garment to cool, then place the transfer face down on the garment. Using medium to firm pressure, press for 25 seconds. Allow transfer to cool before removing silicone paper in an even motion.

WASHING - It is recommended that you wait at least 24 hours prior to washing the garment for the first time. For the initial wash, turn garment inside out & wash separately in cool water, but ALWAYS wash the garment inside out! **Immediately remove garment from washer & put in dryer on warm setting. If left wet in the washer the inks may bleed.** NEVER use bleach or aggressive cleaning agents. To iron the shirt, do not put iron directly on the transferred area.

STORAGE - Return unused portion of paper to a sealed bag. Keep product in a cool, dry environment away from heating and cooling sources.

Technical Support Toll Free: 877-437-8556; Fax: 918-437-8588

Copyright © 2015, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107 877-437-8556