

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS



LOVE what you PRESS!



DecoFILM® *Paint FX*

- Pearlescent transfer films that resemble the shimmer of car paint
- Pressure sensitive PET liner enables easy repositioning
- Adds considerable value that direct screen printing cannot reproduce
- Can be used on sport and leisure wear



Black
DFPX-5480



Green
DFPX-5481



Blue
DFPX-5482



Champagne
DFPX-5484



Pink
DFPX-5485



Purple
DFPX-5486

Application Instructions

Cotton, Uncoated Polyester, Fabric blends, Spandex, Lycra, Wool, Linen



45° Blade



Cut this
material in
mirror image



310°F - 330°F



Firm, even
pressure.
Cover & reheat
if necessary



17 - 20
seconds



Peel warm,
then repress
for 2 seconds



Wash inside out,
cold water, gentle
cycle. Dry low heat.
Suitable for dry-cleaning.

No nylon.

*Instructions for application to moisture-wicking materials:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then rub it into the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

*Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2014, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107