

LOVE what you **PRESS!** 

PoliMelt

PM-700

Polimelt is used to bond foils to garments.

Application Instructions

Cotton, Uncoated Polyester, Cotton/Polyester, Polyester/Acrylic



45° Blade



315°F - 330°F



PRESS

Medium
even
pressure



15 - 20
seconds



PEEL

Peel warm



Wash warm,
tumble dry
normal. Suitable
for dry-cleaning.

No nylon, dazzle cloth, or shiny polyester. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.

***Damp a cloth with rubbing alcohol (isopropyl alcohol), then gently apply it to the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow the adhesive to better penetrate the garment.**

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2014, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107

LOVE what you **PRESS!** 

PoliMelt

PM-700

Polimelt is used to bond foils to garments.

Application Instructions

Cotton, Uncoated Polyester, Cotton/Polyester, Polyester/Acrylic



45° Blade



315°F - 330°F



PRESS

Medium
even
pressure



15 - 20
seconds



PEEL

Peel warm



Wash warm,
tumble dry
normal. Suitable
for dry-cleaning.

No nylon, dazzle cloth, or shiny polyester. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.

***Damp a cloth with rubbing alcohol (isopropyl alcohol), then gently apply it to the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow the adhesive to better penetrate the garment.**

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2014, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107