Specialty Materials
THE BEST GARMENT DECORATION PRODUCTS

LOVE what you PRESS!

Thermo Flex® TURBO

Available in 15" and 20" widths only

- Low temperature & quick press time, which eliminates press marks
- Durable, weeds easily, and has a soft hand and strong grip
- Blocks dye-migration since it has a low heat and quick press time
- Pressure-sensitive carrier enables easy weeding and repositioning



★Starred colors cannot be layered beneath another product
These swatches are only representative, due to the limitations of printer inks.

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Thermo Flex® TURBO

Application Instructions for Cotton, Polyester, and Cotton/Polyester Blends



45° Blade



Cut this material in mirror image



270°F



Medium, even pressure



Press for 5 seconds





Machine wash using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not iron directly onto this material. Wash temperature should not exceed 140°F.

Application Instructions for Nylon



45° Blade



Cut this material in mirror image



300°F



Low. even pressure



Pre-press garment for 5 seconds, press material for 5 seconds



Peel Warm, cover with silicone sheet and re-press for 10 seconds



Machine wash using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not iron directly onto this material. Wash temperature should not exceed 140°F.





Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.